

PROFESSIONAL EQUIPMENT

Vulcaflex Line

10VB48

Safety boot with polypropylene toe cap, padded collars, made of leather, side elastic closure, internal lining and dual density sole.



Technical Specifications:

Polypropylene toe cap

Padded collars

Relax leather upper

Internal lining

Antibacterial hygienic insole

PU dual density sole

Uppers: Black relax leather from

15 to 17 lines thick

Trinforcement: Termoplastic 1,5mm thick

Tread: Polyamide nº 30.

Standard: NBR ISO 20347:2015

Sizes: From 33 to 47

Warranty: 36 months

Color: Black

Approval Certificate: 43377



Sole: Made of two layers of polyurethane, directly injected in the upper; softer and lighter midsole (first layer) - density 0,4g/cm³, providing more comfort; and more compact sole (second layer) – density 0,9g/cm³, sharp objects and abrasion resistant with antislip system made up of special grooves, 3mm height, 6mm width and resistant to slipping on ceramic and steel floors (SRC Level).



Upper and strap Lining:

Non-woven in short fibers with a minimum 1,9 thickness.

Toe cap: Polypropylene injected plastic, 1,5mm thick. P.S: this kind of toe cap does not have the same safety properties of the the steel cap.

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

Single shoe weight: 0,324kg

Height leg: 115mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size.

Product Package

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)
- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)


Technologies



woven made of polyester fibers that ensure greater softness, lightness and convenience to users

Segmentos







General Services

Service Providers