

# **Composite Line**

## 50B19 C

Safety boot with composite toe cap, padded collars, made of leather, side elastic closure, internal lining and dual density sole.

# **Technical Specifications:**

Composite Toe Cap

Cowhide Leather Uppers

Padded collars

Internal Lining

Antibacterial hygienic insole

PU dual density sole with electrical

hazard resistance

Uppers: Cowhide leather from 18 to 20 lines thick

Trinforcement: Termoplastic 1,5mm thick

Tread: Nylon nº 30.

Standard: NBR ISO 20345:2015

Sizes: From 33 to 47

Warranty: 36 months

Color: Black

Approval Certificate: 18051

**Obs:** Class I insulating footwear has the purpose of insulation in low voltage electrical installations up to 500 V in dry conditions. The test voltage which is 14,000 V or 14 KV is the voltage under which the footwear is subjected to verification of its properties (the leakage current is verified).

Hygienic Insole: Anatomically conform in EVA antifugal/antibacterial, made up of micro-stitches providing sweat absorption and desorption.

Assembly insole: Upper sewed by strobel system, resin and needle-polyester - 2,0mm thick

## Technologies

#### arcon

Air confort woven made of polyester fibers that ensure greater softness, lightness and convenience to users



Composite TOE Comfortable, lightweight and impact-resistant composite non-metallic toe cap. withstanding 200J impact and compression up to 1500 N according to NBR ISO 20345/2015.

Upper and strap Lining:Toe capNon-woven in shortwithstafibers with a minimumcompresentation

top cap covering.

1,9 thickness.

Sole: Made of two layers of polyurethane, directly

more compact sole (second layer) - density

injected in the upper; softer and lighter midsole (first

0,9g/cm<sup>3</sup>, sharp objects and abrasion resistant with

antislip system made up of special grooves, 3mm height and 6mm width, 600V electrical resistant and

layer) - density 0,4g/cm<sup>3</sup>, providing more comfort; and

Toe cap: ultra-resilient polymer, withstanding 200J impact and compression up to 1500Kg (N) and 51% lighter than steel toe caps. It also has antimagnetic and anti-corrosive properties besides being undetectable by metal detectors.

## Single shoe weight: 0,559kg

Height leg: 114mm

Obs.: height leg is based on size 40 and it may vary 3,33 mm per size.

## **Product Package**

Plastic bag in collective box

- Sizes: L 565mm x W 300mm x H 245mm (collective box for up to 5 pairs)

- Sizes: L 414mm x W 315mm x H 505mm (collective box for up to 10 pairs)

# Segmentos







Note: warranty begins from the date of production of the shoe

marluvas.com.br

facebook/MarluvasEquipamentos

(32) 3693 4000